

PRODUCT DATASHEET LED Classic Stick 60 P 8.5W 827 Frosted E27

LED CLASSIC STICK P | LED lamps, classic stick shape



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Attractive lamp appearance
- Instant 100 % light, no warm-up time
- Made of recycled plastics, the lamp contributes to the reduction of CO2 emissions and landfill waste

Product features

- LED alternative to conventional lamps
- Lifetime up to 15,000 h
- Not dimmable
- Minimum 50 % of recycled plastic (out of total plastic weight) used
- Good quality of light; color rendering index R_{a} : \geq 80; constant chromaticity






TECHNICAL DATA

Electrical data

Nominal wattage	8.5 W
Construction wattage	8.50 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	60 W
Nominal current	60 mA
Type of current	AC
Inrush current	7.04 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	30
Max. lamp number on MCB B16 A	36
Total harmonic distortion	104.40 %
Power factor λ	0.63

Photometrical data

Luminous flux	806 lm
Luminous efficacy	94 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



LISO spectral power distribution 2700K CRI80 v1

Light technical data

Beam angle	240 °
Warm-up time (60 %)	0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	118.00 mm
Diameter	37.00 mm
Maximum diameter	37 mm
Product weight	28.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	90 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	9.00 kWh/1000h

Energy consumption

9.00 kWh/1000h

Type of protection

IP20

Standards

CE / UKCA / EAC

Photobiological safety group acc. to EN62778

RG0

Country-specific categorizations

Temperature range at storage

Order reference

LOGISTICAL DATA		

LED STICK60 8,5

-40...+80 °C

Energy labelling regulation data acc EU 2019/2015

Lighting technology used Non-directional or directional Non-directional or directional Mains or non-mains MLS Light source cap-type (or other electric interface) E27 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source Anti-glare shield No Correlated colour temperature type Standby power LED NDLS NDLS NO E27 No No SINGLE_VALUE Standby power	
Mains or non-mains Light source cap-type (or other electric interface) E27 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE	
Light source cap-type (or other electric interface) Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type E27 No No Single_VALUE	
Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE	
Color-tuneable light source Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type No	
Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE	
High luminance light source Anti-glare shield No Correlated colour temperature type SINGLE_VALUE	
Anti-glare shield No Correlated colour temperature type SINGLE_VALUE	
Correlated colour temperature type SINGLE_VALUE	
Standby power 0.00 W	
Claim of equivalent power Yes	
Length 118.00 mm	
Height 37.00 mm	
Width 37.00 mm	
Chromaticity coordinate x 0.4578	
Chromaticity coordinate y 0.4101	
R9 Colour rendering index 1	
Beam angle correspondence SPHERE_360	

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Survival factor	0.90
Displacement factor	0.912
LED light source replaces a fluorescent light source	No
EPREL ID	523290,1838210,2190100
Model number	AC31132,AC55960,AC69376,AC69376

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LED Stick lamp
PDF	Declarations of conformity	LED CLASSIC / LED STICK
PDF	Declarations of conformity	Declaration of conformity CE
PDF	Declarations of conformity UKCA	LED CLASSIC / LED STICK
PDF	Declarations of conformity UKCA	UKCA declaration LED stick
	District the state of the state	
	Photometric and lighting design files	Document name
	Spectral power distribution	LISO spectral power distribution 2700K CRI80 v1

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854057113	Folding box 1	42 mm x 42 mm x 121 mm	41.00 g	0.21 dm ³
4099854057120	Shipping box 10	218 mm x 92 mm x 132 mm	420.00 g	2.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.