

PRODUCT DATASHEET LED Spot Stamp 2xGU10 White and Wood

LED Spot Stamp | Ceiling mounted luminaires made with mixed materials with adjustable GU10 spotlights



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, bedrooms, basements

Product benefits

- Flexible thanks to replaceable LED lamps
- Easy mounting

Product features

- Luminaire family features four versions with up to 4 spot heads
- Housing material: metal and wood
- On/off switch on 1-head version for easy operation
- Adjustable heads




TECHNICAL DATA

Electrical data

| Nominal voltage | 220240 V |
|------------------|--|
| Mains frequency | 5060 Hz |
| Protection class | T. Control of the con |
| Operating mode | Mains voltage |

Dimensions & Weight

| Length | 255.00 mm |
|----------------|-----------|
| Width | 90.00 mm |
| Height | 148.00 mm |
| Product weight | 485.00 g |



LED SPOT STAMP 2XGU10 WT

Materials & Colors

| Product color | White Wood decor |
|--|------------------|
| Housing color | White Wood decor |
| Body material | Steel Rubberwood |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|------------------------------|-------------------------|
| Temperature range at storage | -20+80 °C |
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Wall / Ceiling |
| Adjustable | Yes |

| With light source | No |
|--------------------------|------|
| Replaceable light source | No |
| Holder designation | GU10 |

Emergency lighting

| Type of emergency operation test | None |
|----------------------------------|------|
|----------------------------------|------|

Certificates & Standards

| Standards | CE / UKCA |
|--|-----------|
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |

Additional product data

| Product remark | Maximum bulb wattage: 5 W LED / Available from October 2025 |
|-----------------------|---|
| Number of illuminants | 2 |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|--|--------------------------|--|
| POF | User instruction / safety instructions | LED SPOT STAMP G11238937 | |
| PDF | Declarations of conformity | LED SPOT CE declaration | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075852600 | Folding box 1 | 112 mm x 172 mm x 302 mm | 664.00 g | 5.82 dm ³ |
| 4058075852617 | Shipping box 4 | 365 mm x 245 mm x 325 mm | 3106.00 g | 29.06 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.