

## PRODUCT DATASHEET

# Orbis Larios 490mm 36W 830 Click DIM Wood Decor and White

Orbis Larios | LED ceiling luminaire with plastic ring



### Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

### Product benefits

- Aesthetic and functional product design
- Click dim function by wall switch

### Product features

- Ceiling luminaire with advanced LED technology
- Click-DIM version: dimmable in three steps by repeated switching
- Color temperature: 3,000 K
- Type of protection: IP20



TECHNICAL DATA

Electrical data


|                        |               |
|------------------------|---------------|
| Nominal wattage        | 36.00 W       |
| Nominal voltage        | 220...240 V   |
| Mains frequency        | 50...60 Hz    |
| Nominal current        | 180.000 mA    |
| Power factor $\lambda$ | 0.90          |
| Protection class       | I             |
| Operating mode         | Mains voltage |

Photometrical data

|                                                |            |
|------------------------------------------------|------------|
| Luminous flux                                  | 2000 lm    |
| Total luminous flux of contained light sources | 4700 lm    |
| Luminous efficacy                              | 56 lm/W    |
| Color temperature                              | 3000 K     |
| Light color (designation)                      | Warm White |
| Color rendering index Ra                       | > 80       |
| Standard deviation of color matching           | 6 sdcn     |
| Flickering metric (Pst LM)                     | <1         |
| Stroboscope effect metric (SVM)                | <0.4       |
| Photobiological safety group acc. to EN62778   | RG0        |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 490.00 mm |
| Height         | 80.00 mm  |
| Product weight | 1820.00 g |



## Materials & Colors

|                                            |                                                                       |
|--------------------------------------------|-----------------------------------------------------------------------|
| Product color                              | White Wood decor                                                      |
| Housing color                              | White Wood decor                                                      |
| Body material                              | Metal                                                                 |
| Cover material                             | Poly methyl methacrylate (PMMA) Acrylonitrile butadiene styrene (ABS) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                                                                |

## Application & Mounting

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ambient temperature range              | -20...+40 °C                |
| Temperature range at storage           | -20...+80 °C                |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP20                        |
| Protection class IK (shock resistance) | IK03                        |
| Dimmable                               | Yes                         |
| Type of dimming                        | 3 DIM                       |
| Mounting type                          | Surface                     |
| Mounting location                      | Ceiling                     |
| With light source                      | Yes                         |
| Replaceable light source               | No                          |

## Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 50000 h <sup>1)</sup> |
| Number of switching cycles | 15000                 |

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Emergency lighting

|                                  |      |
|----------------------------------|------|
| Type of emergency operation test | None |
|----------------------------------|------|

## Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA       |
| Luminaire with limited surface temperature, "D sign" | No              |
| Ball shot safe                                       | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

## EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

### Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                       |                                        | Document name          |
|----------------------------------------------------------------------------------|----------------------------------------|------------------------|
|  | User instruction / safety instructions | G11242730 ORBIS LARIOS |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                 |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4099854618383 | Folding box<br>1             | 88 mm x 513 mm x 513 mm              | 2373.00 g    | 23.16 dm <sup>3</sup>  |
| 4099854618390 | Shipping box<br>4            | 530 mm x 360 mm x 530 mm             | 10442.00 g   | 101.12 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.