

PRODUCT DATASHEET Outdoor Flex 20M RGB IP65 Remote Control

Outdoor Flex Strips IP65 RGB | Robust and extendable LED Strip, RGB



Areas of application

- Gardens and other outdoor areas
- Suitable for indoor and outdoor applications (IP65)

Product benefits

- Bright, robust and durable

Product features

- Extendable up to 50 meters, max. 450 W
- Protection class (strip): IP65
- Protection class (power supply): IP44
- RGB color control

TECHNICAL DATA

Electrical data

Nominal wattage	135.00 W
Nominal voltage	220240 V
Type of current	AC
Mains frequency	5060 Hz
Power factor λ	> 0.90


Photometrical data

Light color (designation)	Red / Green / Blue
Standard deviation of color matching	< 6 sdcm

Light technical data

Beam angle	120 °

Dimensions & Weight



Length	20000.00 mm
Width	16.00 mm
Height	8.00 mm
Product weight	4610.00 g

Colors & materials

Product color	White
Body material	Polyvinyl chloride (PVC)

Lifespan

Number of switching cycles	10000

Capabilities

Dimmable	Yes
Lowest bending radius	70,0 mm
Self-adhesive	No

Certificates & Standards

Standards	CE
Protection class	П
Type of protection	IP65

LOGISTICAL DATA

Temperature range at storage -20+80 °C
--

EQUIPMENT / ACCESSORIES

- Equipped with 1.5 m cable and plug
- Cable reel for easy storage
- Remote control and battery included
- Mounting accessories included

Safety advice

- Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Outdoor Flex UI/SI
PDF	Declarations of conformity	Outdoor Flex RGB Declaration of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075848825	Folding box	207 mm x 292 mm x 370 mm	4928.00 g	22.36 dm ³
4058075848832	Shipping box 2	440 mm x 315 mm x 398 mm	10708.00 g	55.16 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.