

PRODUCT DATASHEET

LED Spot Cylinder 2xGU10 Brushed Nickel

LED Spot Cylinder | Surface mounted luminaires with adjustable GU10 spotlights

Areas of application

- Indoor applications



Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

Product features

- Luminaire family features four versions with up to 4 spot heads
- Housing surface made of brushed nickel
- Adjustable head
- On/off switch on 1-head version for easy operation




TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Length	254.00 mm
Width	65.00 mm
Height	134.00 mm
Product weight	294.00 g



LED SPOT CYLINDER 2XGU10

Materials & Colors

Product color	Brushed nickel
Housing color	Brushed nickel
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
Adjustable	Yes

With light source	No
Replaceable light source	Yes
Holder designation	GU10

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Product remark	Maximum bulb wattage: 5 W LED / Available from January 2026
Number of illuminants	2

Safety advice

- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED SPOT CYLINDER G11239548
	Declarations of conformity	LED Spotlights
	Declarations of conformity UKCA	LED Spotlights

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075852785	Folding box 1	82 mm x 106 mm x 262 mm	373.00 g	2.28 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075852792	Shipping box 4	218 mm x 170 mm x 270 mm	1665.00 g	10.01 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.