

# PRODUCT DATASHEET

## LN COMP SWITCH 1200 14 W 3000 K

LINEAR COMPACT SWITCH | Compact single or light line luminaire with switch



### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Accent lighting
- Public areas
- Cove lighting
- Shelves, furniture integration or under cabinet mounting
- Seamless linear lighting



### Product benefits

- Compact dimensions
- Little space required thanks to compact dimensions
- Seamless connection of up to 10 luminaires in a line
- Handy switch directly installed on the luminaire
- Low flicker light thanks to special electronic control gear
- Flexible installation in 2 different angles with 2 different mounting options
- Flexible application due to a wide range of available lengths of 300 to 1500 mm.
- Angled connection possible with included cable

### Product features

- Built-in switch
- Up to 10 luminaires connectable



- Translucent end caps
- Versions with luminous flux 400...1900 lm available
- 5 different lengths available
- High luminous efficacy: up to 112 lm/W
- Glow Wire Test according to IEC 60695-2-12: 850 °C


---

**TECHNICAL DATA****Electrical data**

|                                                             |                   |
|-------------------------------------------------------------|-------------------|
| Nominal wattage                                             | 14.00 W           |
| Nominal voltage                                             | 220...240 V       |
| Mains frequency                                             | 50...60 Hz        |
| Nominal current                                             | 115 mA            |
| Inrush current                                              | 10 A              |
| Inrush current time $T_{h50}$                               | 160 $\mu$ s       |
| Max. number of luminaires per miniature circuit breaker B16 | 41                |
| Max. number of luminaires per miniature circuit breaker C10 | 35                |
| Max. number of luminaires per miniature circuit breaker C16 | 56                |
| Power factor $\lambda$                                      | > 0.5             |
| Total harmonic distortion                                   | 89 %              |
| Protection class                                            | II                |
| Operating mode                                              | Integrated driver |

**Photometrical data**


|                                              |                      |
|----------------------------------------------|----------------------|
| Luminous flux                                | 1400 lm              |
| Luminous efficacy                            | 100 lm/W             |
| Color temperature                            | 3000 K               |
| Light color (designation)                    | Warm White           |
| Color rendering index Ra                     | > 80                 |
| Standard deviation of color matching         | < 5 sdc <sub>m</sub> |
| Luminous intensity                           | -                    |
| Low flicker                                  | Yes                  |
| Photobiological safety group acc. to EN62778 | RG0                  |
| Beam angle                                   | 140 °                |



LN COMP SWITCH 1200 14W  
3000K 230V IP20

Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1173.00 mm |
| Width          | 28.00 mm   |
| Height         | 36.00 mm   |
| Product weight | 410.00 g   |



LN COMP SWITCH 1200

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | White              |
| Housing color                              | White              |
| RAL Color (most similar)                   | RAL 9016           |
| Body material                              | Polycarbonate (PC) |
| Cover material                             | Polycarbonate (PC) |
| Light emitting surface material            | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 850 °C             |
| Mercury content                            | 0.0 mg             |

Application & Mounting

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

|                                        |                              |
|----------------------------------------|------------------------------|
| Type of connection                     | Screw terminal, 2-Pole (L,N) |
| Type of protection                     | IP20                         |
| Protection class IK (shock resistance) | IK03                         |
| Dimmable                               | No                           |
| Mounting type                          | Surface                      |
| Mounting location                      | Ceiling / Wall               |
| Application environment                | Indoor                       |
| With light source                      | Yes                          |
| Replaceable light source               | No                           |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 50000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 40000 h <sup>1)</sup> |
| Lifespan L80/B50 at 25 °C  | 40000 h               |
| Lifespan L90/B10 at 25 °C  | 30000 h               |
| Number of switching cycles | 100000                |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

|                |        |
|----------------|--------|
| Output current | 190 mA |
|----------------|--------|

### Certificates & Standards

|                                                      |                               |
|------------------------------------------------------|-------------------------------|
| Standards                                            | CE / CB / TÜV SÜD / EAC / EPD |
| Luminaire with limited surface temperature, "D sign" | No                            |
| Ball shot safe                                       | No                            |
| EPD                                                  | LEDV-00018-V01.01-EN          |
| Replaceable light source (EPREL)                     | Not replaceable               |

### EQUIPMENT / ACCESSORIES

- Equipped with power plug, cable connector and line adapter for connecting further luminaires
- Mounting material for wall and ceiling installations included

### Safety advice

- All electrical connections must be made by a qualified person.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's

reach.

## DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                                               |
|------------------------------------------------------------------------------------|----------------------------------------|-------------------------------------------------------------|
|    | User instruction / safety instructions | Linear_Compact_Switch_UI                                    |
|    | On-Pack-Info                           | Legal Insert Linear Compact                                 |
|    | Legal information                      | LS Insert LN COMP HO and SWITCH                             |
|    | Legal information                      | Informationstext 18 Abs 4 ElektroG                          |
|    | Declarations of conformity             | Attestation of Conformity Linear Comp                       |
|    | Declarations of conformity             | EU Declaration of Conformity Linear Comp Switch and HO LEDV |
|   | Declarations of conformity UKCA        | LN COMP SWITCH                                              |
| Photometric and lighting design files                                              |                                        | Document name                                               |
|  | IES file (IES)                         | LN COMP SWITCH 1200 14W 3000K 230V IP20                     |
|  | LDT file (Eulumdat)                    | LN COMP SWITCH 1200 14W 3000K 230V IP20                     |
|  | ULD file (DIALux)                      | LINEARCOMPACTSWITCH120014W3000K                             |
|  | ROLF file (RELUX)                      | LN COMP SWITCH 1200                                         |
|  | UGR file (UGR table)                   | LN COMP SWITCH 1200 14W 3000K 230V IP20                     |
|  | Light distribution curve type polar    | LN COMP SWITCH 1200 14W 3000K 230V IP20                     |
| CAD/BIM files                                                                      |                                        | Document name                                               |
|  | BIM Revit 3D                           | Linear Compact                                              |
|  | CAD STEP 3D                            | LN COMP SWITCH 1200                                         |


| Tender texts                                                                                       | Document name                             |
|----------------------------------------------------------------------------------------------------|-------------------------------------------|
|  Tender documents | LINEAR COMPACT SWITCH 1200 14 W 3000 K-EN |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075106154 | Folding box<br>1             | 1,380 mm x 40 mm x 30 mm             | 525.00 g     | 1.66 dm³  |
| 4058075106161 | Shipping box<br>25           | 1,418 mm x 223 mm x 180 mm           | 11710.00 g   | 56.92 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.